

## LED T8 Lamp Ready Retrofit Strip (2 Pack)

RS SERIES



Lamp Listed



### PRODUCT DESCRIPTION:

The MaxLite Lamp Ready Retrofit Strip provides a UL listed retrofit kit for industrial linear fixtures that is engineered to operate the latest single ended LED T8 lamps supplied separately. Able to be used to retrofit 4' linear fixtures or with a tandem bracket for 8' linear fixture, these retrofit kits come pre-wired for single ended operating LED lamps for contractor ready installation. These retrofit kits are packaged in 2 packs with a tandem bracket included for ease of installation.

**Single ended or Dual mode (Single/Double ended) T8 internal driver lamps (4') under 17W must be purchased separately from Maxlite for this product.**

Refer to Maxlite website for the latest offering.

<https://www.maxlite.com/products/ul-type-b-ballast-bypass-t8/>

<https://www.maxlite.com/products/ul-type-b-ballast-bypass-double-ended-power-t8/>

### FEATURES:

- Sockets are wired in series via non-shunted sockets
- Retrofits into preexisting linear fixtures
- Tandem bracket can be used to turn two 4' sections into 8' retrofit
- Product packaged as 2 pack of 4ft strips for easier 8ft retrofit
- 5 year limited warranty

### CONSTRUCTION:



- Engineered and UL rated to take up to 22w per set of lamp holders
- Wiring is 18 AWG solid to allow 120-277v operation where lamp specification allows
- Sockets rated to 660w , 600V, UL Listed

### ORDERING INFORMATION

| ORDER NUMBER | MODEL     | WATTS (NOMINAL) | DESCRIPTION                               |
|--------------|-----------|-----------------|-------------------------------------------|
| 107768       | RS-482XT8 | 44W             | RETROFIT STRIP 48" 2 LAMP T8 LED 120-277V |



G13LPNS



### NOTES:

1. This product is specifically engineered and listed for use with MaxLite Single Ended conductor LED lamps. Maximum lamp wattages cannot exceed stated levels without voiding warranty. Cannot use with any other brand of lamps.

**SPECIFICATIONS:**

| RS-482XT8     |                       |                                                                                                |
|---------------|-----------------------|------------------------------------------------------------------------------------------------|
| ITEM          | SPECIFICATION         | DETAILS                                                                                        |
| ELECTRICAL    | Input Voltage         | Max 22W Per Lamp                                                                               |
|               | Power Consumption     | Per Lamp Spec                                                                                  |
| PHYSICAL      | Dimension             | 6.5" x 48"                                                                                     |
|               | Housing               | Steel                                                                                          |
|               | Operating Temperature | Per Lamp Spec                                                                                  |
| CERTIFICATION | Certification         | UL for single ended LED lamps*                                                                 |
|               | Material Usage        | RoHS compliant; no mercury                                                                     |
|               | Environment           | Indoor / Damp                                                                                  |
|               | Warranty              | 5 years. Check <a href="http://maxlite.com/warranties">maxlite.com/warranties</a> for details. |

\* See reference diagram adjacent. Must be followed

## IMPORTANT WARNING:

