



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11552 - 5.5 Watt LED PL 2-PIN Dual Mode; 3500K; 500 Lumens; GX23 base; 50000 Average rated hours; 120 deg. Beam Angle; Type A/B Ballast Dependent or Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	6.14
EA Width	0.94
EA Length	1.34
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	PL 2-Pin
Status	Active
Style	Transitional
Most Current Generation	S29881
CCT Selectable	False
Wattage Selectable	False
Finish Family	White
Amps	0.046-0.020A
Has Camera	False
IOT Enabled	False
Lens Finish	Frost
Lens Material	Glass
Lensed	True
Operating Position	Universal
Power Factor	0.97
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	13W
Incandescent Equivalent	45W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	500L
Volts	120V-277V
Watts	5.5W

PHYSICAL

Lamp Base	GX23
Finish	Frost
Housing Color	White
ANSI Base	GX23
Lamp Type	PL
MOD Lamps	1.26
MOL	5.98

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	False

PACKAGING

UPC	045923115523
Case Cube	0.3781
Case Height	7.09
Case Length	16.14
Case Quantity	50
Case UPC	10045923115520
Case Weight	7.72
Case Width	5.71
EA Cube	0.0045
EA Height	6.14
EA Length	1.34
EA Quantity	1
EA Weight	0.15
EA Width	0.94
Inner Cube	0.0624
Inner Height	6.61
Inner Length	5.31
Inner Quantity	10
Inner UPC	20045923115527
Inner Weight	1.54
Inner Width	3.07
Pack Type	Box
Web Length	5.98
Web Width	1.26

COMPLIANCE

CA Regulations	Exempt - Base Not Regulated
FCC Compliant	True
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	False
Title 20	Exempt
T24 Compliant	False